

SO-SFP-L120D-Dxxxx

1062.5 Mb/s ~ 2.67 Gb/s DWDM Multirate SFP

INTRODUCTION

The SO-SFP-L120D-Dxxxx transceiver family are small form factor pluggable modules for bi-directional serial optical data communications. The modules fulfill ITU G.692 and operate at ITU DWDM wavelengths. The SO-SFP-L120D-Dxxxx meet requirements of ITU G.957 (SDH/SONET), IEEE 802.3 Gigabit Ethernet standard and ANSI Fibre Channel specifications, and are suitable for interconnections in WDM, SDH, Gigabit Ethernet and Fibre Channel environments.

The modules are hot pluggable and enhanced digital diagnostic functions are available via an I²C serial bus specified in the SFP MSA SFF-8472. Its multirate characteristics allow the module to transmit data-stream with data-rates up to 2.67 Gb/s. Typical protocols are STM-16FEC/OC-48FEC, STM-16/OC-48, 2G Fibre Channel, Gigabit Ethernet and 1G Fibre Channel.

DWDM modules operate at Dense Wavelength Division Multiplexing (DWDM) wavelengths. There are 45 wavelengths available from 1529.55 nm – 1564.68 nm in 100 GHz (~0.8 nm) channel spacing. The DWDM characteristics are fully compliant to the wavelength parameters specified in ITU standards G.692 and G.694.1

APPLICATIONS




- 1062.5 Mb/s to 2.67 Gb/s
- Ethernet IEEE 802.3ae
- Fibre Channel
- OC-48/STM-16/OTN-1 DWDM Systems

FEATURES

- 45 DWDM lambdas (λ): 1529.55 nm – 1564.68 nm
- Link budget with ADP receiver: 28dB
- Hot-Pluggable SFP footprint LC Optical Transceiver
- Small Form-Factor Pluggable (SFP) MSA compatible
- SFF-8472 Digital Diagnostic Function
- Fully compliant to ITU G.692 & G.694.1
- RoHS compliance

LASER SAFETY

This singlemode transceiver is a Class 1 laser product. It complies with IEC-60825 and FDA 21 CFR 1040.10 and 1040.11. The transceiver must be operated within the specified temperature and voltage limits. The optical ports of the module need to be terminated with an optical connector or a dust plug.



Specification subject to change without notice.

Ordering Information:

Part no:	Description/Application
SO-SFP-L120D-Dxxxx**	1.0625 Mb/s ~ 2.67 Mb/s transceiver operating at DWDM for 180 km of SM fiber

** xxxx = 9160 ~ 9600:

1564.68 nm = 191.60 THz = 9160

1529.55 nm = 196.00 THz = 9600

Optical Parameters:

Part no. \ Parameter	Wavelength [nm]	Opt. Output Power [dBm]	Opt. Receiver Sensitivity [dBm]	Power Budget [dB]
SO-SFP-L120D-Dxxxx	DWDM	+0 to +4	-28	30